



Compact Tilt

IP44 7W/830 36D CA ACC SAT

Compact Tilt is a high-quality adjustable downlight for general lighting in residential buildings and public spaces. This adjustable unit is suitable both for general lighting and for highlighting details. It is dimmable, which offers additional options for atmospheric lighting in the space. Typical applications include hotels, restaurants, lobbies and wet spaces. With three housing-colour options and two colour temperatures, you can select the models that best suit your needs. Compact Tilt Dim models can be mounted directly in the insulation material. The 5 W models can be installed in a ceiling space of 22 mm.

Compact Tilt Downlight 7W 3000K 600lm Beam angle 36°; Casambi; IP44; IK02; Protection cl. II; L70B50 90000h; LED not exchangeable; CRI>80; SDCM3; Suitable for through wiring; 3x1.5mm²; Housing al; Colour ni; Cover Plastic, transparent



IP44 7W/830 36D CA ACC SAT

| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
|--------------|-----------|-----|----------------|
| A1C0DI-CA | A1C0DI-CA | 0.2 | Compact Tilt |

| Mounting | |
|--|-----------------------------|
| Suitable for surface mounting | No |
| Suitable for recessed mounting | Yes |
| Suitable for wall mounting | No |
| Suitable for suspended mounting | No |
| Suitable for ceiling mounting | Yes |
| Suitable for traverse mounting | No |
| Suitable for pedestal/floor mounting | No |
| Suitable for light-track mounting | No |
| Suitable for clamp-mounting | No |
| Suitable for low voltage cable system | No |
| Degree of protection (IP) | IP44 |
| Degree of protection (IP), rear side | IP20 |
| Degree of protection (IP), front side | IP44 |
| Impact strength | IK02 |
| Emergency function monitoring system | None |
| Type of wiring | Suitable for through wiring |
| Number of poles | 3 |
| Conductor cross section (mm ²) | 1.5 |
| Connectable conductor cross section (min) (mm ²) | 0.75 |
| Connectable conductor cross section (max) (mm ²) | 1.5 |
| Connection type | Screwless terminal |
| Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24 | Yes |
| Max. number of luminaires per miniature circuit breaker B16 | 100 |
| Max. number of luminaires per miniature circuit breaker C16 | 200 |
| Fit for workplace acc. EN 12464-1 | No |
| Luminaire may be covered with thermally insulating material | No |
| Structure | |
| Adjustability | Swivelling |
| Lamp type | LED not exchangeable |
| Light source included | Yes |
| Suitable for number of lamps | 1 |
| Lamp holder | Other |
| Housing material | Aluminium |
| Surface protection | Untreated |
| Housing colour | Nickel |
| Cover material | Plastic, transparent |
| Surface brushed | Yes |
| Control gear included | Yes |
| Exchangeable control gear | Yes |
| Reflector | High-gloss |
| Reflector colour | Silver |
| Energy efficiency class of light source according to EU regulation 2019/2015 | F |
| Containing product according to 2019/2020/EU | Yes |
| Emergency power supply system | None |
| Emergency power supply integrated | No |
| Filament test according to IEC 60695-2-11 | 650 °C - 30 s |

| Dimming and control | |
|---|---------|
| With movement sensor | No |
| With presence indicator | No |
| With light sensor | No |
| Dimmable | Yes |
| Dimming 0-10 V | No |
| Dimming 1-10 V | No |
| Dimming DALI-2 | No |
| Dimming DALI | No |
| Dimming DMX | No |
| Dimming DSI | No |
| Dimming potentiometer (integrated) | No |
| Dimming LineSwitch | No |
| Dimming manufacturer's proprietary system | No |
| Dimming mains voltage modulation | No |
| Dimming trailing edge | No |
| Dimming leading edge | No |
| Dimming programmable | Yes |
| Dimming RF | No |
| Dimming Sine Wave Reduction | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming with push-button | No |
| No dimming function | No |
| Constant luminous flux control | No |
| IFTTT support available | No |
| Compatible with Apple HomeKit | No |
| Bluetooth operated | Yes |
| Compatible with Google Assistant | No |
| Compatible with Casambi | Yes |
| Compatible with Amazon Alexa | No |
| Wireless lighting control | Casambi |

| Photometric data | |
|---|-----------------------|
| Light distributor | Reflector |
| Light sharing | Symmetric |
| Beam angle | Medium beam 20-40° |
| Light outlet | Direct |
| Colour of light (alphanumeric) | White |
| Colour temperature (min) (K) | 3000 |
| Colour temperature (max) (K) | 3000 |
| Colour temperature switchable | No |
| Colour rendering index (CRI/Ra) | 80-89 |
| Luminous flux (min) (lm) | 600 |
| Luminous flux (max) (lm) | 600 |
| Effective luminous flux (lm) | 600 |
| Rated luminous flux according to IEC 62722-2-1 (min) (lm) | 600 |
| Rated luminous flux according to IEC 62722-2-1 (max) (lm) | 600 |
| Lumen setting adjustable | No |
| Flickering value Pst LM | 1 |
| Beam angle adjustable | No |
| Stroboscope effect value SVM | 0.4 |
| Photobiological safety according to EN 62471 | RG0 |
| Colour consistency (McAdam ellipse) | SDCM3 |
| Unified Glare Rating (UGR) | 22 |

| Lifetime and capacity | |
|---|-------|
| Rated life time L70/B50 at 25 °C (h) | 90000 |
| Rated life time L80/B50 at 25 °C | 60000 |
| Lumen maintenance at median useful life of 35,000 hrs at 25 °C ambient (tq) (%) | 95 |
| Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%) | 90 |
| Failure rate at median useful life of 35,000 hrs at 25 °C ambient (tq) (%) | 5 |
| Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%) | 5 |
| Rated ambient temperature acc. IEC62722-2-1 (min) (°C) | 0 |
| Rated ambient temperature acc. IEC62722-2-1 (max) (°C) | 25 |

| Measurements | |
|--------------------------------|------|
| Length (mm) | 90 |
| Width (mm) | 90 |
| Height/depth (mm) | 40 |
| Outer diameter (mm) | 90 |
| Built-in length (mm) | 80 |
| Built-in width (mm) | 80 |
| Built-in width (min) (mm) | 80 |
| Built-in width (max) (mm) | 80 |
| Built-in height/depth (mm) | 35 |
| Installation height (min) (mm) | 2000 |
| Installation height (max) (mm) | 6000 |
| Recess diameter (min) (mm) | 80 |
| Recess diameter (max) (mm) | 80 |

| Electrotechnical data | |
|---|---|
| Voltage type | AC |
| Nominal voltage (min) (V) | 220 |
| Nominal voltage (max) (V) | 240 |
| Nominal current (min) (mA) | 332 |
| Nominal current (max) (mA) | 367 |
| Type of control gear | LED operating device current-controlled |
| Total harmonic distortion (THD) (%) | 20 |
| Total harmonic distortion | 20 |
| Protection class according to IEC 61140 | II |
| Suitable for lamp power (min) (W) | 7 |
| Suitable for lamp power (max) (W) | 7 |
| Maximum system power (W) | 7 |
| Luminaire efficacy (min) (lm/W) | 86 |
| Luminaire efficacy (max) (lm/W) | 86 |
| Power factor | 0.9 |
| Luminaire efficacy (lm/W) | 86 |