

Direct M

IP20 3450lm 940 36D WH


Spotlight

Direct M is an energy-efficient and adjustable spotlight with a long lifespan. Its compact size, high-quality light, and excellent color rendering make it an excellent choice for public spaces. Applications include stores, shops, hotels and restaurants. Direct is installed on a track, making its installation easy and flexible. The luminaire has an almost invisible driver integrated directly into the track adapter. The Direct M model is particularly well-suited for store lighting. Its light output and adjustability offer numerous options for illuminating store spaces; the luminaire is easy to move and redirect as needed. Adjusting the direction of the light provides options for illuminating different spaces; the luminaire is easy to move and direct as needed.

Direct M Spotlight 26W 4000K 3450lm Beam angle Medium beam 20-40°; No dim; IP20; IK02; Protection cl. II; L70B50 100000h; LED not exchangeable; Lamp included; CRI>90; SDCM3; Ending; 5x0.75mm²; Housing al; Colour wh; Cover Glass transparent; C16 max. 85

Stocked: No

IP20 3450lm 940 36D WH			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
	A1DIRK	0.48	Direct M



IP20 3450lm 940 36D WH

EC001744 Downlight / spot luminaire / floodlight

Mounting	
Suitable for surface mounting	No
Suitable for recessed mounting	No
Suitable for wall mounting	No
Suitable for suspended mounting	No
Suitable for ceiling mounting	No
Suitable for traverse mounting	No
Suitable for pedestal/floor mounting	No
Suitable for light-track mounting	Yes
Suitable for clamp-mounting	No
Suitable for low voltage cable system	No
Degree of protection (IP)	IP20
Degree of protection (IP), rear side	IP20
Degree of protection (IP), front side	IP20
Impact strength	IK02
Emergency function monitoring system	None
Type of wiring	Ending
Number of poles	5
Conductor cross section (mm ²)	0.75 mm ²
Connectable conductor cross section (min) (mm ²)	1.5 mm ²
Connectable conductor cross section (max) (mm ²)	2.5 mm ²
Connection type	Busbar adapter
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Max. number of luminaires per miniature circuit breaker B16	53
Max. number of luminaires per miniature circuit breaker C16	85
Fit for workplace acc. EN 12464-1	No
Luminaire may be covered with thermally insulating material	-

Structure	
Adjustability	Rotating and swivelling
Lamp type	LED not exchangeable
Light source included	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Aluminium
Surface protection	Powder coating
Housing colour	White
Cover material	Glass transparent
Surface brushed	No
Control gear included	Yes
Exchangeable control gear	No
Reflector	Matt
Reflector colour	Silver
Energy efficiency class of light source according to EU regulation 2019/2015	D
Containing product according to 2019/2020/EU	Yes
Emergency power supply system	None
Emergency power supply integrated	No
Filament test according to IEC 60695-2-11	650 °C - 30 s

Dimming and control	
With movement sensor	No
With presence indicator	No
With light sensor	No
Dimmable	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI-2	No
Dimming DALI	No
Dimming DMX	No
Dimming DSI	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
Constant luminous flux control	No
IFTTT support available	No
Compatible with Apple HomeKit	No
Bluetooth operated	No
Compatible with Google Assistant	No
Compatible with Casambi	No
Compatible with Amazon Alexa	No

Electrotechnical data	
Voltage type	AC/DC
Nominal voltage (min) (V)	220 V
Nominal voltage (max) (V)	240 V
Nominal current (min) (mA)	700 mA
Nominal current (max) (mA)	700 mA
Type of control gear	LED operating device current- controlled
Total harmonic distortion (THD) (%)	20 %
Total harmonic distortion	20 THD
Protection class according to IEC 61140	II
Suitable for lamp power (min) (W)	26 W
Suitable for lamp power (max) (W)	26 W
Maximum system power (W)	26 W
Luminaire efficacy (min) (lm/W)	133 lm/W
Luminaire efficacy (max) (lm/W)	133 lm/W
Power factor	0.9
Luminaire efficacy (lm/W)	123 lm/W

Photometric data	
Light distributor	Reflector
Light sharing	Symmetric
Beam angle	Medium beam 20-40°
Light outlet	Direct
Colour of light (alphanumeric)	White
Colour temperature (min) (K)	4000 K
Colour temperature (max) (K)	4000 K
Colour temperature switchable	No
Colour rendering index (CRI/Ra)	90-100
Luminous flux (min) (lm)	3450 lm
Luminous flux (max) (lm)	3450 lm
Effective luminous flux (lm)	3450 lm
Rated luminous flux according to IEC 62722-2-1 (min) (lm)	3450 lm
Rated luminous flux according to IEC 62722-2-1 (max) (lm)	3450 lm
Lumen setting adjustable	No
Flickering value Pst LM	1
Beam angle adjustable	No
Stroboscope effect value SVM	0.4
Photobiological safety according to EN 62471	RG0
Colour consistency (McAdam ellipse)	SDCM3
Unified Glare Rating (UGR)	21

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	100000 h
Rated life time L80/B50 at 25 °C	100000 h
Lumen maintenance at median useful life of 35,000 hrs at 25 °C ambient (tq) (%)	95 %
Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	90 %
Lumen maintenance at median useful life of 100,000 hr at 25 °C ambient (tq)	80 %
Failure rate at median useful life of 35,000 hrs at 25 °C ambient (tq) (%)	5 %
Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	5 %
Failure rate at median useful life of 100,000 hrs at 25 °C ambient (tq)	10 %
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	0 °C
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	25 °C

Measurements	
Length (mm)	85 mm
Width (mm)	85 mm
Height/depth (mm)	100 mm
Outer diameter (mm)	85 mm
Installation height (min) (mm)	3000 mm
Installation height (max) (mm)	6000 mm