




Office DI

1245 46W/840 AA AL MA WH D/I

The suspension-mounted Office D/I is a diffuse light office luminaire range in which the downlight and uplight can be controlled separately. Thanks to its modular design, the luminaire is easy to customise. Its optics features include an aluminium parabolic louvre and integrated opal shield, which eliminate glare from the LEDs and achieve a low Unified Glare Rating I/value (UGR <19). The luminaire is delivered with a 2-metre cable. Typical applications include schools, offices and other spaces where computers are used.

Office DI Suspension luminaire 46W 4000K 5500lm
Dim programmable; IP20; IK02; Protection cl. I;
L80B10 100000h; LED not exchangeable; Lamp
included; CRI>80; SDCM3; Ending; 5x1mm²; Housing
Steel; Colour wh; Cover Plastic matt/satinized



1245 46W/840 AA AL MA WH D/I			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
A10FCD-AA	A10FCD-AA	3 kg	Office DI

Mounting	
Suitable for light line configuration	No
Fit for workplace acc. EN 12464-1	Yes
Degree of protection (IP)	IP20
Impact strength	IK02
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	Yes
Suitable for emergency lighting	No
Emergency function monitoring system	None
Type of wiring	Ending
Connectable conductor cross section (min) (mm ²)	1.5
Connectable conductor cross section (max) (mm ²)	2.5
Number of poles	5
Conductor cross section (mm ²)	1
Connection type	Other

Structure	
Lamp type	LED not exchangeable
Light source included	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Steel
Housing colour	White
Cover material	Plastic matt/satinized
Type of grid	Matt
Control gear included	Yes
Exchangeable control gear	Yes
Reflector	Matt
Energy efficiency class of light source according to EU regulation 2019/2015	D
Containing product according to 2019/2020/EU	Yes
Emergency power supply integrated	No
Emergency power supply system	None
Filament test according to IEC 60695-2-11	650 °C - 30 s
Suspension supplied with the product	No
Pendant length (min) (mm)	500
Pendant length (max) (mm)	2000

Dimming and control	
Dimmable	Yes
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming potentiometer (integrated)	No
Dimming programmable	Yes
Dimming RF	No
Dimming LineSwitch	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	No
With movement sensor	No
With presence indicator	No
With light sensor	No
Constant luminous flux control	Yes
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
Compatible with Casambi	No
IFTTT support available	No
Bluetooth operated	Yes
Wireless lighting control	ActiveAhead

Photometric data	
Light distributor	Reflector
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct/indirect
Direct-/indirect proportion separately controllabl	Yes
Rated luminous flux according to IEC 62722-2-1 (min) (lm)	5500
Rated luminous flux according to IEC 62722-2-1 (max) (lm)	5500
Effective luminous flux (lm)	5500
Colour of light (alphanumeric)	White
Colour temperature (min) (K)	4000
Colour temperature (max) (K)	4000
Colour rendering index (CRI/Ra)	80-89
Unified Glare Rating (UGR)	19
Flickering value Pst LM	1
Stroboscope effect value SVM	0.4
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	100000
Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	90
Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	5

Measurements	
Width (mm)	140
Height/depth (mm)	60
Length (mm)	1245

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Type of control gear	LED operating device current-controlled
Protection class according to IEC 61140	I
Luminaire efficacy (min) (lm/W)	120
Luminaire efficacy (max) (lm/W)	120
Suitable for lamp power (min) (W)	46
Suitable for lamp power (max) (W)	46
Maximum system power (W)	46
Luminaire efficacy (lm/W)	120
Power factor	0.9