



## Flat Sq

### 120 IP44 9W/840 DA2 PCO WH

Luminaires in the Flat Sq downlight range are suitable for mounting on a low ceiling structure. They are designed for use in bathrooms, corridors and lobbies. The luminaire is dimmable. Equipped with spring terminal blocks, these luminaire can also be linked.

Flat Sq Downlight 9W 4000K 500lm Beam angle Open beam; Dim DALI-2; IP44; Protection cl. II; L70B50 60000h; LED not exchangeable; CRI>80; SDCM4; Suitable for through wiring; 2.5mm<sup>2</sup>; Housing al; Colour wh; Cover Plastic, opal



#### 120 IP44 9W/840 DA2 PCO WH

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
A2FLGH-DALI	A2FLGH-DALI	0.34	Flat Sq

Mounting	
Suitable for surface mounting	No
Suitable for recessed mounting	Yes
Suitable for wall mounting	No
Suitable for suspended mounting	No
Suitable for ceiling mounting	Yes
Suitable for traverse mounting	No
Suitable for pedestal/floor mounting	No
Suitable for light-track mounting	No
Suitable for clamp-mounting	No
Suitable for low voltage cable system	No
Degree of protection (IP)	IP44
Degree of protection (IP), rear side	IP20
Degree of protection (IP), front side	IP44
Impact strength	IK03
Emergency function monitoring system	None
Type of wiring	Suitable for through wiring
Number of poles	5
Conductor cross section (mm <sup>2</sup> )	2.5
Connectable conductor cross section (min) (mm <sup>2</sup> )	1.5
Connectable conductor cross section (max) (mm <sup>2</sup> )	2.5
Connection type	Screwless terminal
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Max. number of luminaires per miniature circuit breaker B16	160
Max. number of luminaires per miniature circuit breaker C16	240
Fit for workplace acc. EN 12464-1	No
Luminaire may be covered with thermally insulating material	No

Structure	
Adjustability	Not adjustable
Lamp type	LED not exchangeable
Light source included	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Aluminium
Surface protection	Powder coating
Housing colour	White
Cover material	Plastic, opal
Surface brushed	No
Control gear included	Yes
Exchangeable control gear	Yes
Reflector	None
Energy efficiency class of light source according to EU regulation 2019/2015	F
Containing product according to 2019/2020/EU	Yes
Emergency power supply system	None
Emergency power supply integrated	No
Filament test according to IEC 60695-2-11	650 °C - 30 s

Dimming and control	
With movement sensor	No
With presence indicator	No
With light sensor	No
Dimmable	Yes
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI-2	Yes
Dimming DALI	Yes
Dimming DMX	No
Dimming DSI	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	Yes
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	Yes
No dimming function	No
Constant luminous flux control	No
IFTTT support available	No
Compatible with Apple HomeKit	No
Bluetooth operated	No
Compatible with Google Assistant	No
Compatible with Casambi	No
Compatible with Amazon Alexa	No

Photometric data	
Light distributor	Diffuser lens/optic/panel
Light sharing	Symmetric
Beam angle	Open beam
Light outlet	Direct
Colour of light (alphanumeric)	White
Colour temperature (min) (K)	4000
Colour temperature (max) (K)	4000
Colour temperature switchable	No
Colour rendering index (CRI/Ra)	80-89
Luminous flux (min) (lm)	500
Luminous flux (max) (lm)	500
Effective luminous flux (lm)	500
Rated luminous flux according to IEC 62722-2-1 (min) (lm)	500
Rated luminous flux according to IEC 62722-2-1 (max) (lm)	500
Lumen setting adjustable	No
Flickering value Pst LM	1
Beam angle adjustable	No
Stroboscope effect value SVM	0.4
Photobiological safety according to EN 62471	RG1
Colour consistency (McAdam ellipse)	SDCM4
Unified Glare Rating (UGR)	22

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	50000
Rated life time L80/B50 at 25 °C	35000
Lumen maintenance at median useful life of 35,000 hrs at 25 °C ambient (tq) (%)	80
Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	70
Failure rate at median useful life of 35,000 hrs at 25 °C ambient (tq) (%)	5
Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	10
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	0
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	25

Measurements	
Length (mm)	120
Width (mm)	120
Height/depth (mm)	26.5
Outer diameter (mm)	120
Built-in length (mm)	105
Built-in length (min) (mm)	105
Built-in length (max) (mm)	105
Built-in width (mm)	105
Built-in width (min) (mm)	105
Built-in width (max) (mm)	105
Built-in height/depth (mm)	26.5
Installation height (min) (mm)	2000
Installation height (max) (mm)	5000

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	350
Nominal current (max) (mA)	350
Type of control gear	LED operating device current-controlled
Total harmonic distortion (THD) (%)	15
Total harmonic distortion	15
Protection class according to IEC 61140	II
Suitable for lamp power (min) (W)	9
Suitable for lamp power (max) (W)	9
Maximum system power (W)	9
Luminaire efficacy (min) (lm/W)	55
Luminaire efficacy (max) (lm/W)	55
Power factor	0.9
Luminaire efficacy (lm/W)	55