




# Futura RST

## 1290 IP65 5000lm/840 DA2 GLFR

Futura RST is a reliable industrial luminaire for challenging applications where extra durability is required from the lighting solution. Its applications include warehouses, industrial facilities, shelters, agricultural production premises and other spaces without explosion hazards. The luminaire is made of impact- and chemical-resistant materials. It is equipped with a stainless steel housing and heat-treated hardened glass diffuser.

Futura RST Sealed industrial luminaire 38W 4000K 5000lm Dim DALI-2; Dim programmable; IP65; IK10; Protection cl. I; L70B50 100000h; LED not exchangeable; Lamp included; CRI>80; SDCM3; Through-wired; 5x2.5mm<sup>2</sup>; Housing st; Colour st; Cover Glass matt/satinized; C16 max. 26



1290 IP65 5000lm/840 DA2 GLFR			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
A3FRSH	A3FRSH	2.4	Futura RST

Mounting	
Suitable for wall mounting	Yes
Suitable for suspended mounting	Yes
Suitable for ceiling mounting	Yes
Suitable for recessed mounting	No
Suitable for surface mounting	Yes
Suitable for light line configuration	No
Suitable for clamp-mounting	Yes
Fit for workplace acc. EN 12464-1	No
Degree of protection (IP)	IP65
Degree of protection (IP), rear side	Other
Degree of protection (IP), front side	IP65
Max. number of luminaires per miniature circuit breaker C10 (MCB)	16
Max. number of luminaires per miniature circuit breaker B16	16
Max. number of luminaires per miniature circuit breaker C16	26
Impact strength	IK10
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Suitable for emergency lighting	No
Emergency function monitoring system	None
Luminaire may be covered with thermally insulating material	-
Type of wiring	Through-wired
Number of poles	5
Conductor cross section (mm <sup>2</sup> )	2.5
Connection type	Screwless terminal
Connectable conductor cross section (min) (mm <sup>2</sup> )	1.5
Connectable conductor cross section (max) (mm <sup>2</sup> )	2.5
Quantity of luminaires for MCB C16:	26
Quantity of luminaires for MCB C10:	16
Quantity of luminaires for MCB B16:	16
Quantity of luminaires for MCB B10:	10

Structure	
With mounting material	Yes
Lamp type	LED not exchangeable
Light source included	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Stainless steel
Housing surface protection	Untreated
Housing colour	Stainless steel
Cover material	Glass matt/satinized
Type of grid	None
Control gear included	Yes
Exchangeable control gear	Yes
Energy efficiency class of light source according to EU regulation 2019/2015	D
Containing product according to 2019/2020/EU	Yes
Emergency power supply system	None
Emergency power supply integrated	No
With switch	No
With air slots	No
Filament test according to IEC 60695-2-11	960 °C - 30 s

Dimming and control	
Dimmable	Yes
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	Yes
Dimming DALI-2	Yes
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	Yes
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	No
With presence indicator	No
With movement sensor	No
With light sensor	No
Constant luminous flux control	Yes
Bluetooth operated	No
Compatible with Casambi	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data	
Light distributor	Reflector
Light sharing	Symmetric
Beam angle	Open beam
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Rated luminous flux according to IEC 62722-2-1 (min) (lm)	5000
Rated luminous flux according to IEC 62722-2-1 (max) (lm)	5000
Colour of light (alphanumeric)	White
Effective luminous flux (lm)	5000
Colour temperature (min) (K)	4000
Colour temperature (max) (K)	4000
Flickering value Pst LM	1
Colour rendering index (CRI/Ra)	80-89
Stroboscope effect value SVM	0.4
Photobiological safety according to EN 62471	RG0
Unified Glare Rating (UGR)	24
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	100000
Rated life time L80/B50 at 25 °C	80000
Lumen maintenance at median useful life of 35,000 hrs at 25 °C ambient (tq) (%)	95
Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	90
Failure rate at median useful life of 35,000 hrs at 25 °C ambient (tq) (%)	5
Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	5
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	-25
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	35

Measurements	
Width (mm)	120
Height/depth (mm)	67
Length (mm)	1290

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	157
Nominal current (max) (mA)	173
Type of control gear	LED operating device current-controlled
Protection class according to IEC 61140	I
Suitable for lamp power (min) (W)	38
Suitable for lamp power (max) (W)	38
Luminaire efficacy (min) (lm/W)	132
Luminaire efficacy (max) (lm/W)	132
Maximum system power (W)	38
Luminaire efficacy (lm/W)	132
Power factor	0.9
Total harmonic distortion (THD) (%)	10
Total harmonic distortion	10